

Low Voltage isolation transformers

IMPREGO

Dry-type impregnated transformers

Low Voltage



Tailored to your needs

Your requirements

- Adapt** your installation to the required earthing system
- Protect** your installation from electrical pollution
- Limit** the impact of disturbances and manage them
- Modify** the nominal voltage of your installation
- Safeguard** people and property

Our solutions

- A wide range** of transformers (6.3 to 3 000 kVA)
- Standardized products** up to 400 kVA
- Available quickly**, with some units in stock
- A complete range** of accessories
- & ALWAYS FOCUSED ON YOUR ACTUAL NEEDS**

Three-phase & single-phase dry-type transformers and autotransformers

Ex. of Accessories

Thermal protection



Dampers



Rollers



Standardized ref. (1)

Units in stock,
out in **2 DAYS**

Our commitment,
quality at the
BEST PRICE

Technical characteristics

- Power : 6.3 to 3 000 kVA
- Voltage : from a few Volts to 1.1kV
- Frequency : 50 or 60 Hz
- IEC 61558-2-4 or IEC 60076-11
- Taps on primary or secondary
- Triangle, star or zigzag coupling, with or without neutral
- Isolation class: H
- Aluminium or copper windings
- Tropicalized varnish
- Electrostatic shield between primary & secondary windings
- Self-extinguishing ability **[F1 certif.]**
- Enclosure available as an accessory

⁽¹⁾ **Three-phase transformers** : 8kVA to 400kVA, 400/400V or 400/231V, 50/60Hz, Triangle/Star+neutral, IP00 or IP21, RAL9003
K-factor equivalence for harmonics-polluted networks

Single-phase transformers : 6.3kVA to 20kVA, 231/115 V or 400/231 V, 50/60Hz, IP00 or IP21, RAL9003

Healthcare transformers (IEC 61558-2-15): 3-phase 400/231V, single-phase 231/115-231V, 50/60Hz, IP00 or IP21, RAL9003

Autotransformers : 10kVA to 400kVA, 231/400V or 400/231V, 50/60Hz, IP00 or IP21, RAL9003

Contact us : bcv-technologies@sgb-smit.group tel. +33 (0)2 51 52 22 00 / Visit us at : bcv-technologies.com / Follow us : 